

Service Manual

ORDER NO. **RRV 1729**

FILE-TYPE CD PLAYER F606 PD-F506

Refer to the service manual RRV1457 for PD-F605/KUXJ.

THIS MANUAL IS APPLICABLE TO THE FOLLOWING MODEL(S) AND TYPE(S).

T	Mo	del	Downer Bossies ont	Demode
Туре	PD-F606	PD-F506	Power Requirement	Remarks
KUXJ	0	0	AC120V	
KCXJ	0	0	AC120V	

• For the circuit and mechanism descriptions, refer to the service guide RRV1469 for PD-F605, PD-F505.

CONTENTS

1.	CONTRAST OF MISCELLANEOUS PARTS	2
2.	SCHEMATIC AND PCB CONNECTION DIAGRAMS	4

PIONEER ELECTRONIC CORPORATION

4-1, Meguro 1-Chome, Meguro-ku, Tokyo 153, Japan

PIONEER ELECTRONICS SERVICE, INC. P.O.Box 1760, Long Beach, CA 90801-1760, U.S.A.
PIONEER ELECTRONIC [EUROPE] N.V. Haven 1087, Keetberglaan 1, 9120 Melsele, Belgium
PIONEER ELECTRONICS ASIACENTRE PTE. LTD. 501 Orchard Road, #10-00 Lane Crawford Place, Singapore 0923

1. CONTRAST OF MISCELLANEOUS PARTS

NOTES:

- Parts marked by "NSP" are generally unavailable because they are not in our Master Spare Parts List.
- The ∆ mark found on some component parts indicates the importance of the safety factor of the part. Therefore, when replacing, be sure to use parts of identical designation.
- When ordering resistors, first convert resistance values into code form as shown in the following examples.
- Ex.1 When there are 2 effective digits (any digit apart from 0), such as 560 ohm and 47k ohm (tolerance is shown by J = 5%, and K = 10%)

Ex.2 When there are 3 effective digits (such as in high precision metal film resistors). 5.62k $\Omega \rightarrow 562 \times 10^{i} \rightarrow 5621$ RN1/4PC S62 F

■ CONTRAST TABLE

PD-F606/KUXJ, PD-F606/KCXJ, PD-F506/KUXJ, PD-F506/KCXJ and PD-F605/KUXJ have the same construction except for the following:

				Part No.			
Mark	Symbol & Description	PD-F605	PD-F606	PD-F606	PD-F506	PD-F506	Remarks
		/KUXJ	/KUXJ	/KCXJ	/KUXJ	/KCXJ	
Δ	MOTHER PCB ASSY	PWM1989	PWM2090	PWM2090	PWM2088	PWM2088	
NSP	SUB PCB ASSY	PWX1434	PWX1436	PWX1436	PWX1431	PWX1431	
	FUNCTION PCB ASSY	PWZ3134	PWZ3136	PWZ3136	PWZ3131	PWZ3131	1
NSP	POWER SW PCB ASSY	PWZ3145	PWZ3145	PWZ3145	PWZ3143	PWZ3143	1
	PACKING	1					
	Remote Control Unit	PWW1108	PWW1108	PWW1108	Not used	Not used	1
	Battery Cover	AZN2249	AZN2249	AZN2249	Not used	Not used	
NSP	Battery (R6P, AA)	AEX ~ 010	AEX - 010	AEX - 010	Not used	Not used	i
	Packing Case	PHG2162	PHG2225	PHG2229	PHG2230	PHG2231	1
	Protector F	PHA1299	PHA1309	PHA1309	PHA1309	PHA1309	
	Protector R	PHA1300	PHA1310	PHA1310	PHA1310	PHA1310	
	Operating Instructions (English)	PRB1234	PRB1252	Not used	PRB1252	Not used	
	Operating Instructions (English/French)	Not used	Not used	PRE1250	Not used	PER 1250	
NSP	Warranty Card	ARY1051	ARY1051	ARY1075	ARY1051	ARY1075	
	Polyetylene Bag (0.03×230×34)	Z21 - 038	Z21 - 038	Z21 - 038	Not used	Not used	1
	EXTERIOR						
	Rear Base	PNA2258	PNA2316	PNA2316	PNA2323	PNA2323	1
	Door	PNW2616	PNW2731	PNW2731	PNW2731	PNW2731	
	Control Panel	PNW2649	PNW2704	PNW2704	PNW2719	PNW2719	1
	65 Label	ORW1069	ORW1069	Not used	ORW1069	Not used	Ì
	Display Window	PAM1702	PAM1702	PAM1702	PAM1699	PAM1699	
	36P F.F.C/30V	PDD1173	PDD1173	PDD1173	Not used	Not used	
	32P F.F.C/30V	Not used	Not used	Not used	PDD1167	PDD1167	

■ CONTRAST OF PCB ASSEMBLIES FUNCTION PCB ASSY

PWZ3136, PWZ3131 and PWZ3134 have the same construction except for the following:

	0 1 1 0 0 1 1 1	Part No.						
Mark	Symbol & Description	PWZ3134	PWZ3136	PWZ3131	Remarks			
	R701 - R704 (10KΩ)	ACN7011	Not used	Not used				
	Remote Sensor	SBX1785 - 51	SBX1976 - 51	Not used				
	CN701	HLEM36R - 1	HLEM36R - I	HLEM32R - 1				

POWER SW PCB ASSY

Although PWZ3143 and PWZ3145 are different in part number, they consist of the same components.


MOTHER PCB ASSY
PWM2090, PWM2088 and PWM1989 have the same construction except for the following:

ark	Symbol & Description	PWM1989	Part No. PWM2090	PWM2088	Rem
		 			_
	IC151	CXA1372Q	CXA1372BQ	CXA1372BQ	
	IC301	CXD2508AQ	CXD2519Q	CXD2519Q	
	IC351	PD4674B	PD4815A	PD4815A	
	Q321	DTC124ES	DTC124ES	Not used	
	D321, D391	1SS254	1 SS254	Not used	
	L302, L303, L321	LAU1R0J	Not used	Not used	
	L341	LAU1R2J	Not used	Not used	
	C170	CKCYB332K50	CGCYX333K25	CGCYX333K25	
	C171	CKCYB102K50	CKCYB182K50	CKCYB182K50	
	C301	Not used	CQMA104K50	CQMA104K50	*
	C302	CGCYX473K50	CEAS101M10	CEAS101M10	
	C303	CFTYA104J50	Not used	Not used	1
	C304	CGCYX473K25	CKCYF103Z50	CKCYF103Z50	
		Not used			
	C311 – C314, C316 C317	Not used Not used	CEAS101M10 CKCYF103Z50	CEAS101M10 CKCYF103Z50	*
	1 1777		CNC11103230	CRC11103250	"
	C321	CGCYX104K25	CGCYX104K25	Not used	
	C322	CEAS101M6R3	CEAS101M10	Not used	
	C325	CKCYF103Z50	Not used	Not used	
	C341	CCCCH100D50	CCCCH120J50	CCCCH120J50	
	C342	CKCYB102K50	CCCCH120J50	CCCCH120J50	
	C343	CCCCH220J50	Not used	Not used	
	C356	Not used	CEAS4R7M50	CEAS4R7M50	*
		Not used			
	C364		CKCYF103Z50	CKCYF103Z50	*
	C393	CCCSL101J50	Not used	Not used	
	C398	Not used	CCCSL101J50	CCCSL101J50	*
	C399	Not used	CKCYF103Z50	CKCYF103Z50	*
	C421, C422	CKCYB471K50	Not used	Not used	
	C423 - C426	CCCSL181J50	Not used	Not used	
	C433, C434	CEANP220M10	CEAS220M25	CEAS220M25	
	C435 – C438	CCCSL101J50	Not used	Not used	
	C481, C482	Not used	CCCSL390J50	CCCEL 200150	*
	R160	RD1/4PU274J		CCCSL390J50	•
			Not used	Not used	
	R171	Not used	RD1/4PU362J	RD1/4PU362J	*
	R306	RD1/4PU682J	RDI/4PU222J	RD1/4PU222J	
	R308	RD1/4PU104J	Not used	Not used	
	R309, R487 – R490	Not used	RD1/4PU104J	RD1/4PU104J	*
	R321	RD1/4PU471J	RD1/4PU102J	 Not used 	
	R323	Not used	RD1/4PU152J	Not used	*
	R341	RD1/4PU511J	RD1/4PU271J	RD1/4PU271J	
	R360, R363, R365	RD1/4PU103J	Not used	Not used	
	R385, R386	RD1/4PU221J	Not used	Not used	
	R419 - R422	RD1/4PU562J	Not used	Not used	
	R427 - R430	RD1/4PU153J	Not used	Not used	
	R435, R436	RD1/4PU333J	Not used	Not used	
	R437, R438	RD1/4PU333J	RD1/4PU473J	RD1/4PU473J	
			DD1//PY/000*	nn./:	
	R439 - R442	RD1/4PU563J	RD1/4PU823J	RD1/4PU823J	
	R481, R482, R485, R486	Not used	RD1/4PU223J	RD1/4PU223J	*
	CN351	HLEM36S	HLEM36S	HLEM32S	
	JA301	TOTX178	Not used	Not used	
	JA321	Not used	GP1F32T	Not used	*
	X341	ASS7000	PSS1008	PSS1008	

Note *: Refer to "SCHEMATIC AND PCB CONNECTION DIAGRAMS".


2. SCHEMATIC AND PCB CONNECTION DIAGRAMS

Note: When ordering service parts, be sure to refer to "EXPLODED VIEWS and PARTS LIST" or "PCB PARTS LIST"





Note:

The numbers marked with a circle show the number of each measuring point, which correspond to the number in the service manual PD-F605 (ORDER NO. RRV1457) on page 13.




MOTHER PCB ASSY







Service Manual



ORDER NO. RRV 1 4 5 7

PD-F505

THIS MANUAL IS APPLICABLE TO THE FOLLOWING MODEL(S) AND TYPE(S).

T	Mo	del	Power Poquirement	Remarks
Туре	PD-F605	PD-F505	Power Requirement	nemarks
KUXJ	0	0	AC120V	

CONTENTS

1.	SAFETY INFORMATION	2
2.	PACKING AND PARTS LIST	3
3.	EXPLODED VIEWS AND PARTS LIST	4
4.	SCHEMATIC AND PCB CONNECTION DIAGRAMS.	. 10
5.	PCB PARTS LIST	. 19
6.	ADJUSTMENTS	. 22
7.	FL INFORMATION	. 27
8.	IC INFORMATION	. 28
9.	DISASSEMBLY	. 31
0.	PANEL FACILITIES	. 32
11.	SPECIFICATIONS	. 33
2	BLOCK DIAGRAM	.34

PIONEER ELECTRONIC CORPORATION 4-1, Megu

4-1, Meguro 1-Chome, Meguro-ku, Tokyo 153, Japan

PIONEER ELECTRONICS SERVICE, INC. P.O.Box 1760, Long Beach, CA 90801-1760, U.S.A. PIONEER ELECTRONIC (EUROPE) N.V. Haven 1087, Keetberglaan 1, 9120 Melsele, Belgium

PIONEER ELECTRONICS ASIACENTRE PTE. LTD. 501 Orchard Road, #10-00 Lane Crawford Place, Singapore 0923

1. SAFETY INFORMATION

This service manual is intended for qualified service technicians; it is not meant for the casual do-it-yourselfer. Qualified technicians have the necessary test equipment and tools, and have been trained to properly and safely repair complex products such as those covered by this manual.

Improperly performed repairs can adversely affect the safety and reliability of the product and may void the warranty. If you are not qualified to perform the repair of this product properly and safely, you should not risk trying to do so and refer the repair to a qualified service technician.

WARNING

Lead in solder used in this product is listed by the California Health and Welfare agency as a known reproductive toxicant which may cause birth defects or other reproductive harm (California Health & Safety Code, Section 25249.5).

When servicing or handling circuit boards and other components which contain lead in solder, avoid unprotected skin contact with the solder. Also, when soldering do not inhale any smoke or fumes produced.

NOTICE

(FOR CANADIAN MODEL ONLY)

Fuse symbols — (fast operating fuse) and/or — (slow operating fuse) on PCB indicate that replacement parts must be of identical designation.

REMARQUE

(POUR MODÈLE CANADIEN SEULEMENT)

Les symboles de fusible (fusible de type rapide) et/ou (fusible de type lent) sur CCI indiquent que les pièces de remplacement doivent avoir la même désignation.


-(FOR USA MODEL ONLY)-

1. SAFETY PRECAUTIONS

The following check should be performed for the continued protection of the customer and service technician.

LEAKAGE CURRENT CHECK

Measure leakage current to a known earth ground (water pipe, conduit, etc.) by connecting a leakage current tester such as Simpson Model 229-2 or equivalent between the earth ground and all exposed metal parts of the appliance (input/output terminals, screwheads, metal overlays, control shaft, etc.). Plug the AC line cord of the appliance directly into a 120V AC 60Hz outlet and turn the AC power switch on. Any current measured must not exceed 0.5mA.



ANY MEASUREMENTS NOT WITHIN THE LIMITS OUTLINED ABOVE ARE INDICATIVE OF A POTENTIAL SHOCK HAZARD AND MUST BE CORRECTED BEFORE RETURNING THE APPLIANCE TO THE CUSTOMER.

2. PRODUCT SAFETY NOTICE

Many electrical and mechanical parts in the appliance have special safety related characteristics. These are often not evident from visual inspection nor the protection afforded by them necessarily can be obtained by using replacement components rated for voltage, wattage, etc. Replacement parts which have these special safety characteristics are identified in this Service Manual.

Electrical components having such features are identified by marking with a \triangle on the schematics and on the parts list in this Service Manual.

The use of a substitute replacement component which dose not have the same safety characteristics as the PIONEER recommended replacement one, shown in the parts list in this Service Manual, may create shock, fire, or other hazards.

Product Safety is continuously under review and new instructions are issued from time to time. For the latest information, always consult the current PIONEER Service Manual. A subscription to, or additional copies of, PIONEER Service Manual may be obtained at a nominal charge from PIONEER.

2. PACKING, EXPLODED VIEWS AND PARTS LIST

NOTES:

- Parts marked by "NSP" are generally unavailable because they are not in our Master Spare Parts List.
- The \triangle mark found on some component parts indicates the importance of the safety factor of the part. Therefore, when replacing, be sure to use parts of identical designation.
- Parts marked by " " are not always kept in stock. Their delivery time may be longer than usual or they may be unavailable.

■ CONTRAST OF PD-F605 AND PD-F505


PD-F505 and PD-F605 have the same construction except for the following:

Marile	No.	No. Symbol & Description	Part	No.	Remarks
Mark		Symbol & Description	PD-F605	PD-F505	Homarks
	2 3 4 10	Remote Control Battery Cover Battery (R6P, AA) Packing Case	PWW1108 AZN2249 AEX – 010 PHG2162	Not used Not used Not used PHG2156	

■ PARTS LIST FOR PD-F605

Mark	No.	Description	Parts No.	<u>Mark</u>	No.	Description	Parts No.
	1	Operating Instructions (English)	PRB1234		11	Packing Sheet	AHG7010
	2	Remote Control Unit	PWW1108	NSP	12	Warranty Card	ARY1051
	3	Battery Cover	AZN2249		13	Polyethylene Bag	Z21 - 038
NSP	4	Battery (R6P, AA)	AEX - 010				
	5	Cord with Mini Plug	PDE1247				
	6	Cord with Plug	PDE1248				
	7						
	8	Protector F	PHA1299				
	9	Protector R	PHA1300				
	10	Packing Case	PHG2162				

PACKING



3. EXPLODED VIEWS AND PARTS LIST

NOTES:

- Parts marked by "NSP" are generally unavailable because they are not in our Master Spare Parts List.
- The \triangle mark found on some component parts indicates the importance of the safety factor of the part. Therefore, when replacing, be sure to use parts of identical designation.
- Parts marked by " " are not always kept in stock. Their delivery time may be longer than usual or they may be unavailable.

3.1 EXTERIOR


■ CONTRAST OF PD-F505 AND PD-F605

PD-F505 and PD-F605 have the same construction except for the following:

A4		Owner of C December	Part	No.	0
Mark	No.	Symbol & Description	PD-F605	PD-F505	Remarks
Δ	1	Mother PCB ASSY	PWM1989	PWM1984	
	2	Function PCB ASSY	PWZ3134	PWZ3129	
	5	36P F.F.C/30V	PDD1173	Not used	
	5	32P F.F.C/30V	Not used	PDD1167	
	10	Rear Base	PNA2258	PNA2241	
	43	Display Window	PAM1702	PAM1699	
	48	Panel	PNW2649	PNW2617	
NSP	50	Power SW PCB ASSY	PWZ3145	PWZ3143	

■ PARTS LIST FOR PD-F605

Mark	No.	Description	Parts No.	Mark	No.	Description	Parts No.
\triangle	1	Mother PCB ASSY	PWM1989		31	Servo Cover	ANW7073
	2	Function PCB ASSY	PWZ3134		32	Nice Cover	ANW7074
Δ	3	Cord Stopper	CM - 22C		33	Screw P	PBA1105
	4	22P F.F.C/30V	PDD1170		34	Screw C	PBA1106
	5	36P F.F.C/30V	PDD1173	NSP	35	C.H.Spacer	PEB1295
lack	6	AC Power Cord	PDG1015		36	Damper ASSY 80	PXA1584
$\Delta\!$	7	Power Transformer	PTT1237	NSP	37	GM Mechanism	AXA7026
	8	Bonnet	PYY1187		38	Disc Rack Panel	AAK7251
NSP	9	Under Base	PNA2249		39	Rubber Sheet	AEB1111
	10	Rear Base	PNA2258		40	Power Button	PAC1815
	11	F.B Stopper	PNB1565		41	Operate Button	PAC1816
	12	Panel Angle	PNB1545		42	Name Plate	PAM1608
	13	Hood Angle L	PNB1546		43	Display Window	PAM1702
	14	Hood Angle R	PNB1547		44	Door Spring	PBH1216
	15	Home Lock Angle 1	PNB1548	NSP	45	Cushion (ART. SVEDE)	PED1016
	16	Home Lock Angle 2	PNB1549		46	Hood	PNW2613
	17	Barrier	PNB1550		47	Door	PNW2616
	18	Foot ASSY	AEC1531		48	Panel	PNW2649
	19	Link Spring	PBH1215		49	Assist Spacer	PNM1295
	20	Link Spacer	PEB1292	NSP	50	Power SW PCB ASSY	PWZ3145
	21	Link	PNW2614	NSP	51	Home SW PCB ASSY	PWZ3149
	22	FFC Holder	PNW2615	NSP	52	Hood SW PCB ASSY	PWZ3151
	23	Cord Clamper	RNH - 184		53		
NSP	24	Locking Card Spacer	VEC1596		54	Screw	BBZ30P060FMC
	25	Rack Spring	ABH7057		55	Screw	BBZ30P080FZK
	26	Guide Shaft - 25	ALA7007		56	Screw	PPZ30P080FMC
	27	Shaft Holder	ANB7021		57	Screw	FBT40P080FZK
NSP	28	Assist Angle	ANB7043		58	Screw	IBZ30P080FMC
	29	Disc Rack	ANW7069		59	Binder	ZCA – SKB90BK
	30	Rack Base S	ANW7070		60	65 Label	ORW1069
					61	Caution Lavel 25	PRW1423



Parts List

Mark	No.	Description	Parts No.	Mark	No.	Description	Parts No.
NSP	1	Mecha PCB Assy	AWZ7835		51	D.C. Motor Assy	PEA1235
NSP	2	Sensor PCB Assy	AWZ7836		52	Carriage DC Motor Assy	PEA1246
NSP	3	Motor PCB Assy	AWZ7837		53	Pinion Gear	PNW2055
NSP	4	SW PCB Assy	AWZ7838	NSP	54	Carriage DC Motor/0.3W	PXM1027
1101	5	Arm A Spring	ABH7050		55	Disc Table Assy	PEA1314
	6	Gear Plate Spring	ABH7051		56	Mechanism Board Assy	PWX1192
	7	Clamp Spring	ABH7107		57	Guide Bar	PLA1094
	8	Lock Lever Spring	ABH7106		58		
	9	Lock Level Spring	710177100		59	Screw	JFZ17P025FZK
	10	Loading Belt	AEB7029		60	Screw	JFZ20P040FMC
	11	Belt	AEB7030		61	Washer	WT12D032D025
NSP	12	Lock Angle	ANB7027		62	Clamp Magnet	PMF1014
		_			63	Yoke M	PNB1312
NSP	13	Lock Lever	ANB7038	NCD			
NSP	14	Servo Stopper S	ANB7047	NSP	64	Disc Table	PNW2410
	15	Loading Base	ANW7051	NSP	65	Float Angle	ANB7020
	16	Cam Cover	ANW7052		66	Gear Stopper	PNB1303
	17	Motor Holder	ANW7053		67	Screw	BPZ20P060FMC
	18	Sensor Holder	ANW7054		68	Screw	BPZ26P100FMC
	19	Float Base	ANW7088		69		
	20	Clamper Holder	ANW7056		70	Froil	GYA1001
	21	Arm (A)	ANW7057		71	Ha Narl	GEM1016
	22	Arm (B)	ANW7058				
	23	Drive Plate	ANW7059				
	24	Arm Plate	ANW7060				
	25	Gear Plate	ANW7061				
	26	Gear Pulley (B)	ANW7062				
	27	Gear A	ANW7063				
	28	Drive Gear	ANW7064				
	29	Bearing	ANW7065				
	30	Gear Pulley (A)	ANW7066				
	31	Select Gear	ANW7067				
	32	Roller	ANW7068				
	33	LED Lens	ANW7072				
	34	Roller B	ANW7075				
	35	Motor Pulley	PNW1634				
	36	Clamper	PNW2569				
	37	Float Spring	ABH7049				
	38	Connector Assy (4P)	ADE7006				
	39	Float Rubber	AEB7028				
NSP	40	Servo Mechanism Assy GM	AXA7028				
	41	Camus	IPZ20P080FMC				
	41	Screw					
	42	Motor Assy	AEA7005				
NSP	43	Motor	PXM1002				
	44 45	Motor Assy Loading Motor	AEA7006 VXM1034				
	43	Loading Motor	AMILOST				
	46	Gear 1	PNW2052				
	47	Gear 2	PNW2053				
	48	Gear 3	PNW2054				
	49	Carriage Base	PNW2445				
	50	Pickup Assy	AEA7004				
		y					

В

4. SCHEMATIC AND PCB CONNTCTION DIAGRAMS


4.1 GM MECHANISM

NOTE FOR PCB DIAGRAMS:

В

- Part numbers in PCB diagrams match those in the schematic diagrams.
- A comparison between the main parts of PCB and schematic diagrams is shown below.

Symbol in PCB Diagrams	Symbol in Schematic Diagrams	Part Name
© ○ ○ B C E	B C E B C E	Transistor
B C E	B C E B C E	Transistor with resistor
© 0 0 D G 8	D G S D G S	Field effect transistor
<u>000/000</u> 4	[[]"[] ****** 000000	Resistor array
000		3-terminal regulator



 This diagram is viewed from the mounted parts side. The parts mounted on this PCB include all necessary parts for several destinations.

For further information for respective destinations, he sure

For further information for respective destinations, be su to check with the schematic diagram.

10

1

2

3

SW PCB ASSY (AWZ7838)

CC MP

<u>@ 6 0</u>

<u>(660</u>

EJECT

J656 D28PWW9515E

4(T)

(F)57 (T) 57 (G ACTT+

ACTF+

CLMP EJCT

THIST

LEDR

2 LEDG

CN653 SLEM22R-2

SPDR

CADR

∠ (F)

MOTOR PCB ASSY (AWZ 7837)

R653

IT)57

← (F)

J654 D28PWY@5156

R651 R652 56K 10K

△ (T)

D651 VRPG56155 RED GREEN

3 PHTR

R653 DCN1862 R654 DCN1865

R654

SCH-1

CN202 (+SCH-2)

PCB

MOTHER

0

NOTE FOR SCHEMATIC DIAGRAMS

- 1. When ordering service parts, be sure to refer to "PARTS LIST of EXPLODED VIEWS" or "PCB PARTS LIST".
- 2. Since these are basic circuits, some parts of them or the values of some components may be changed for improve-
- 3. RESISTORS:

Unit: k:kΩ, M·MΩ, or II unless otherwise noted. Rated power: 1/4W, 1/6W, 1/8W, 1/10W unless otherwise

Tolerance. (F). ±1%, (G): ±2%, (K) ±10%, (M): ±20% or ±5% unless otherwise noted.

4. CAPACITORS:

Unit. p.pF or µF unless otherwise noted. Ratings: capacitor (µF)/voltage(V) unless othrewise noted. Rated voltage: 50V except for electrolytic capacitors.

Unit: m.mH or µH unless otherwise noted

6. VOLTAGE AND CURRENT:

DC voltage (V) in PLAY mode unless otherwise noted ⇔ mA or ← mA.

DC current in PLAY mode unless otherwise noted. Value in () is DC current in STOP mode.

7 OTHERS:

- ⊘ or ⊘ · Adjusting point
- . Measurement point.
- The A mark found on some component parts indicates the importance of the safety factor of the parts. Therefore, when re-placing, be sure to use parts of identical designation.
- 8. SCH- ON THE SCHEMATIC DIAGRAM:

 SCH-□ indicates the drawing number of the schematic dia gram (SCH stands for schematic diagram.)

9. SWITCHES (Underline indicates switch position): FUNCTION PCB ASSY

S701 : MODE

S702 : CLEAR

S703 : ■ S704 : ◄◄ ◄◄

S705 : ►► ►►

S707 : HI-LITE

S708: PROGRAM

S709 : ►/II

S710 : BEST S711 : DISC -


S712 . DISC +

S713 : RANDOM S714 : REPEAT

S715 : PREVIOUS

POWER SW PCB ASSY S752 : POWER STANDBY/ON

SCH-1



SIGNAL ROUTE

FOCUS SERVO LOOP LINE

TRACKING SERVO LOOP LINE

LOADING MOTOR ROUTE

SPINDLE MOTOR ROUTE CARRIAGE MOTOR ROUTE

AUDIO SIGNAL

GM MECHANISM


GM MECHANISM

SCH-1

2

6


12



13

Ė

MOTHER PCB ASSY, FUNCTION PCB ASSY, POWER SW PCB ASSY, HOME SW PCB ASSY HOOD SW PCB ASSY





PD-F605, PD-F505

Waveforms

Note: The encircled numbers denote measuring point in the schematic disgram.

*2 FOCUS: Press the key without loading a disc.





17

18

5. PCB PARTS LIST

NOTES:

- Parts marked by "NSP" are generally unavailable because they are not in our Master Spare Parts List.
- The \triangle mark found on some component parts indicates the importance of the safety factor of the part. Therefore, when replacing, be sure to use parts of identical designation.
- Parts marked by "6" are not always kept in stock. Their delivery time may be longer than usual or they may be unavailable.
- When ordering resistors, first convert resistance values into code form as shown in the following examples.
- Ex.1 When there are 2 effective digits (any digit apart from 0), such as 560 ohm and 47k ohm (tolerance is shown by J = 5%, and K = 10%).

560Ω	\rightarrow	56 × 10 ¹ → 561	RD1/4PU56[]J
$47k\Omega$	\rightarrow	$47 \times 10^{3} \rightarrow 473 \dots$	RD1/4PU473J
0.5Ω	\rightarrow	OR5	RN2HOR5K
$I\Omega$	\rightarrow	1R0	RSIP I ROK

Ex.2 When there are 3 effective digits (such as in high precision metal film resistors).

 $5.62k\Omega \rightarrow 562 \times 10^{1} \rightarrow 5621$ RN1/4PC [5]6[2][] F

■ LIST OF WHOLE PCB ASSEMBLIES

Manda	Cumbal & Description	Part	No.	Remarks
Mark	Symbol & Description	PD-F605	PD-F505	nemarks
Δ	MOTHER PCB ASSY	PWM1989	PWM1984	
NSP	SUB PCB ASSY	PWX1434	PWX1429	
	FUNCTION PCB ASSY	PWZ3134	PWZ3129	
NSP	POWER SW PCB ASSY	PWZ3145	PWZ3143	
NSP	-HOME SW PCB ASSY	PWZ3149	PWZ3149	
NSP	HOOD SW PCB ASSY	PWZ3151	PWZ3151	
NSP	GM MECHANISM	AXA7026	AXA7026	
NSP	LO MECHANISM BOARD ASSY	AWX7013	AWX7013	
NSP	⊢MECHA PCB ASSY	AWZ7835	AWZ7835	
NSP	- SENSOR PCB ASSY	AWZ7836	AWZ7836	
NSP	MOTOR PCB ASSY	AWZ7837	AWZ7837	
NSP	└─SW PCB ASSY	AWZ7838	AWZ7838	
NSP	SERVO MECHANISM ASSY	AXA7028	AXA7028	
NSP	MECHANISM BOARD ASSY	PWX1192	PWX1192	

■ CONTRAST OF PCB ASSEMBLIES

MOTHER PCB ASSY

PWM1984 and PWM1989 have the same construction except for the following:

Mark	Symbol &	Part No.					
Mark	Description	PWM1989	PWM1984				
	C321	CGCYX104K25	Not used				
	C322	CEAS101M6R3	Not used				
	C325	CKCYF103Z50	Not used				
	CN351	HLEM36S - 1	HLEM32S - 1				
İ	D321, D391	1SS254	Not used				
	JA301 Optical Output Jack	TOTX178	Not used				
	L321	LAU010J	Not used				
	Q321	DTC124ES	Not used				
	R321	RD1/4PU102J	Not used				

FUNCTION PCB ASSY

PWZ3129 and PWZ3134 have the same construction except for the following:

Mark	Symbol &	Part No.					
Mark	Description	PWZ3134	PWZ3129				
	CN701 Remote Sensor	HLEM36R - 1 SBX1785 - 51	HLEM32R - 1 Not used				

POWER SW PCB ASSY

Although PWZ3143 and PWZ3145 are diffirent in part number, they consist of the same components.

PD-F605, PD-F505

■ PCB PARTS LIST FOR PD-F605

<u> Mark</u>	No. Descr	iption	Parts No.	Mark	No.	Descr	iption	Parts No.
MO.	THER PCB	ASSY			C309		ELECT. CAPACITOR	CEASR47M50
					C310		CERAMIC CAPACITOR	CKCYF103Z5
:FM	CONDUCTO	RS			C321		CERAMIC CAPACITOR	CGCYX104K2
	IC151	SERVO IC	CXA1372O		C322		ELECT. CAPACITOR	CEAS101M6R
A		POWER OP – AMP IC	LA6520		C325		CERAMIC CAPACITOR	CKCYF103Z5
$\stackrel{\Lambda}{\Sigma}$	IC21	REGULATOR IC	PQ05RR12					
۲.	IC301	EFM DEMODULATION IC			C341		CERAMIC CAPACITOR	CCCCH100D5
	IC351	SYSTEM. CONTROL	PD4674B		C342		CERAMIC CAPACITOR	CKCYB102K5
	10331	STSTEM. CONTROL	I D-1074B		C343		CERAMIC CAPACITOR	CCCCH220J5
	10405	OP - AMP IC	NJM4558D – D		C351		ELECT. CAPACITOR	CEAS471M6R
	IC405		DTC124ES			C354	CERAMIC CAPACITOR	CKCYF103Z5
	Q321	TRANSISTOR	2SK246		C333,	, 05.74	CERTIFIC CHITCHES	0.10.1.100.00
	Q341	N - FET			C361		CERAMIC CAPACITOR	CKCYF103Z5
	Q403, Q404	TRANSISTOR	2SD2144S		C393		CERAMIC CAPACITOR	CCCSL101J50
	Q405	TRANSISTOR	DTC124ES			C422	CERAMIC CAPACITOR	CKCYB471K
								CCCSL181J50
7	D11 - D14	DIODE	S5688G			- C426	CERAMIC CAPACITOR	CEANP220M
	D218	DIODE	1SS254		C433.	, C434	ELECT. CAPACITOR	CEANF220M
	D321, D341	DIODE	1SS254		C425	G430	CER ANG CARACITOR	CCCSI IOLISC
	D391 – D394		1SS254			- C438	CERAMIC CAPACITOR	CCCSL101J50
7	D52	DIODE	S5688G		C441	, C442	CERAMIC CAPACITOR	CKCYB152K
	D54	ZENNER DIODE	MTZJ18B	RESI	STOF	RS		
					VR15	1, VR15	2 VR (22kΩ)	RCP1046
٦II	S AND FILT	ERS					Other Resistors	RD1/4PU□□□
	L302, L303	AXIAL INDUCTOR	LAU010J					
	L321	AXIAL INDUCTOR	LAU010J	OTHI	ERS			
	L341	AXIAL INDUCTOR	LAUIR2J		CN20)1	CONNECTOR 6P	RKP - 533
	L351	AXIAL INDUCTOR	LAU100J		CN20)2	CONNECTOR 22P	HLEM22S - 1
	L391	AXIAL INDUCTOR	LAU010J		CN35	51	CONNECTOR 36P	HLEM36S - 1
	2371				JA30	1	OPTICAL OUTPUT JACK	TOTX178
ΔP	ACITORS				JA39	1, JA392	JACK	RKN1004
••	C11, C13	CERAMIC CAPACITOR	CKCYF103Z50					
	C15 - C17	CERAMIC CAPACITOR	CKCYF103Z50		JA40	1	JACK	PKB1023
	C25	ELECT. CAPACITOR	CEAS332M16		X341		XTAL RES (OSC)	ASS7000
	C26	ELECT. CAPACITOR	CEAS102M16				(33.8688MHz)	
	C27	ELECT. CAPACITOR	CEAS330M16		X351		CERAMIC RESONATOR	VSS1014
	C21	DDD : O'III TOIL	02.10000.110				(4.19MHz)	
	C52	ELECT. CAPACITOR	CEAS101M35					
	C155	CERAMIC CAPACITOR	CKCYB561K50	Δ			TERMINAL	RKC - 061
	C156	CERAMIC CAPACITOR	CGCYX333K25					
	C150	CERAMIC CAPACITOR	CGCYX103K25	FUN	CTI	ON PO	CB ASSY	
	C158, C159	CERAMIC CAPACITOR	CGCYX104K25					
	C136, C139	CERAMIC CAPACITOR	COCTATOAR25	SEM	CON	DUCTO	ORS	
	C160	ELECT CAPACITOD	CEAS4R7M50				DIODE	1SS133
	C160	ELECT. CAPACITOR			2,01	2,03		
	C161	CERAMIC CAPACITOR	CGCYX104K25	ewit	CHE	SAND	RELAYS	
	C162	ELECT. CAPACITOR	CEAS4R7M50	31111			SWITCH	PSG1006
	C163	CERAMIC CAPACITOR	CGCYX104K25		3/01	-3/13	SWILCH	1501000
	C164	CERAMIC CAPACITOR	CGCYX103K25	CAP	CIT)De		
			O11 O1 TO 1 O1 TO 1	CAP			CED AMIC CARACITOR	CKCYF103Z
	C167	CERAMIC CAPACITOR	CKCYF103Z50		C701		CERAMIC CAPACITOR	CKCIFIU3Z
	C168	CERAMIC CAPACITOR	CGCYX333K25	252	OTO-	20		
	C169	CERAMIC CAPACITOR	CGCYX103K25	RES	-		PROTECTION (COLO)	ACNIBOLL
	C170	CERAMIC CAPACITOR	CKCYB332K50		R701	- R704	RESISTOR ($10k\Omega$)	ACN7011
	C171	CERAMIC CAPACITOR	CKCYB102K50					
				OTH				
	C172	CERAMIC CAPACITOR	CKCYB472K50		CN7	01	CONNECTOR	HLEM36R -
	C205, C210	CERAMIC CAPACITOR	CKCYF103Z50		V701		FL INDICATOR TUBE	PEL1089
	C215	CERAMIC CAPACITOR	CKCYF103Z50				REMOTE SENSOR	SBX1785 - 5
	C218	CERAMIC CAPACITOR	CGCYX103K25					
	C219	CERAMIC CAPACITOR	CKCYF103Z50	POV	VER	SW F	PCB ASSY	
	G202	CED AMIC CARACITOR	CCCVV473V35	ewin	CHE	SAND	RELAYS	
	C302	CERAMIC CAPACITOR	CGCYX473K25	34411	S752		SWITCH	PSG1006
		AUDIO FILM CAPACITOR	CFTYA 104 J 50		3/32		SWITCH	F301000
	C303		000000					
	C304	CERAMIC CAPACITOR	CGCYX473K25					
			CGCYX473K25 CKCYB152K50 CGCYX473K25					

Mark No. Description Parts No. **HOME SW PCB ASSY SWITCHES AND RELAYS** DSG1048 S811 PUSH SWITCH **HOOD SW PCB ASSY SWITCHES AND RELAYS** S821 PUSH SWITCH DSG1015 **OTHERS** 3P JUMPER WIRE D20PWW0305E J821 **MECHA PCB ASSY SEMICONDUCTORS** O651 TRANSISTOR DTC124ES VRPG5615S D651 LED **RESISTORS** RESISTOR(56kΩ) ACN7012 R651 ACN7011 R652 RESISTOR($10k\Omega$) CARBON FILM RESISTOR DCN1062 R653 $(220\Omega, 1/6W)$ R654 RESISTOR(0Ω) DCN1065 **OTHERS** CN651 4P CONNECTOR 173979 - 4 12FMZ - AST 12P CONNECTOR CN652 22P CONNECTOR **SLEM22R - 2** CN653 **SENSOR PCB ASSY SEMICONDUCTORS** PHOTO INTERRUPTER **GP1S24** D652 **OTHERS** D20PWW0315E 3P JUMPER WIRE J652 **MOTOR PCB ASSY OTHERS** LOADING MOTOR VXM1034 SW PCB ASSY **SWITCHES AND RELAYS** VSG1006 S651, S652 PUSH SWITCH OTHERS D20PWW0315E **3P JUMPER WIRE** J656 **MECHANISM BOARD ASSY SWITCHES AND RELAYS** PUSH SWITCH **DSG1016** S610

173979 - 4


OTHERS

CN610


6. ADJUSTMENTS (調整方法)

6.1 PREPARATIONS (準備)


1.1 Jigs and Measuring Instruments (使用測定器/治工具類)




1.2 Necessary Adjustment Points (調整に必要な項目)





1 How to Start/Cancel Test Mode (テストモ-ドの設定/解除)





6.3 Check and Adjustment (確認、調整)















7. FL INFORMATION


■ PEL1089 (V701 : FUNCTION PCB ASSY)

• FL TUBE


PIN LOCATION



GRID ASSIGNMENT



COLOR OF ILLUMINATION Blue-green: Unless specified segment color Mandarin : 7/1///



PIN CONNECTION

Assignment

Pin No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	50
Assignment	F	F	NP	116	10G	96	86	7G	6G	56	4 G	36	26	16	NL	NL	NL	P	r	a
Pin No.	21	55	23	24	25	26	27	28	29	30	31	32	33	34						

NOTE) F: Filament 1G~11G: Grid a~h, j, k, m, n, p, r: Anode NP: No Pin NL: No Lead

NP F F

8. IC INFORMATION


- The information shown in the list is basic information and may not correspond exactly to that shown in the schematic diagrams.
- **CXD2508AQ (IC301 : MOTHER PCB ASSY)**
- Digital signal processor for CD

DTS2 79

DTS3 80

• Pin Arrangement BCK PCMD PCMD LRCKI WDCK EMPH DOUT C4M FSTT MNT0 MNT1 XROF C2PO VSS XPCK XUGF GTOP BCKI GFS 64 63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 ASYE ZEROR 66 39 ASYO DTS1 38 ASYI 37 BIAS VDD 68 36 RF 35 AVDD1 CXD2508AQ AVDD2 34 CLTV 33 AVSS1 AVDD3 (Top view) 32 VDD XTAI 31 PCO XTAO 30 FILI AVSS3 29 FILO AVSS2 28 TEST NRPWM 27 LOCK RPWM

• Block Diagram



26 MDS

25 MDP

• Pin Function

No.	Pin Name	1/0	Function
1	SCOR	0	H when detecting subcode sync. either S0 or S1.
2	SBSO	0	Serial output of SUBP - W.
3	EXCK	1	Clock input for SBSO lead out.
4	sqso	0	Serial output of SUBQ 80 bit.
5	SQCK	ı	Clock input for SQSO lead out.
6	MUTE	1	Mute for H and release for L (DAC section).
7	SENS	0	SENS output to CPU.
8	XRST	1	System reset. Reset for L.
9	DATA	ı	Serial data input from CPU.
10	XLAT	1	Latch input from CPU and latch the serial data at falling edge.
11	CLOK	ı	Serial data transferring clock input from CPU.
12	VSS	_	GND.
13	SEIN	1	Sens input from SSP.
14	CNIN		Count signal siput of track jump.
15	DATO	0	Serial data output to SSP.
16	XLTO	0	Serial data latch output to SSP and latch at falling edge.
17	CLKO	0	Serial data transferring clock output to SSP.
18	SPOA	ı	Microcomputer expansion interface. (Input A)
19	SPOB	1	Microcomputer expansion interface. (Input B)
20	SPOC	1	Microcomputer expansion interface. (Input C)
21	XTSL	ı	Xtal selection input pin, L when Xtal is 16.9344MHz and H when Xtal is 33.8688MHz.
22	XLON	0	Microcomputer expansion interface. (Output)
23	FOK	١	Focus OK input pin. Use for SENS output and servo auto sequencer.
24	MON	0	ON/OFF control output of spindle motor.
25	MDP	0	Servo control of spindle motor.
26	MDS	0	Servo control of spindle motor.
27	LOCK	0	Sample the GFS with 460Hz. Houtput when GFS is H and Loutput when GFS is L for series of eight times.
28	TEST	1	TEST pin. GND at normal use.
29	FILO	0	Filter output for master PLL (sleave=digital PLL).
30	FILI	1	Filter input for master PLL.
31	PCO	0	Charge pump output for master PLL.
32	VDD	_	Digital power supply for DSP.
33	AVSS1	_	Analog GND for DSP.
34	CLTV	1	VCO control voltage input for master PLL.
35	AVDD1	_	Analog power supply for DSP.
36	RF	ı	EFM signal input.
37	BIAS	1	Constant-current input of the asymmetry correction circuit.
38	ASYI	1	Comparison voltage input of the asymmetry correction circuit.
39	ASYO	0	EFM full swing output. (L=VSS, H=VDD).
40	ASYE	ı	L : Asymmetry correction OFF, H : Asymmetry correction ON.
41	WDCK	0	D/A interface for 48 bit slot and word clock (2FS) .
42	LRCK	0	D/A interface for 48 bit slot and LR clock (FS).
43.	LRCKI	ī	LR clock input to DAC (48 bit slot).

PD-F605, PD-F505

No.	Pin Name	1/0	Function
44	PCMD	0	D/A interface and serial data (2'SCOMP, MSB fast)
45	PCMDI	ı	Audio data input to DAC (48 bit slot).
46	вск	0	D/A interface and bit clock.
47	ВСКІ	ı	Bit clock input to DAC (48 bit slot).
48	GTOP	0	GTOP output.
49	XUGF	0	XUGF output.
50	XPCK	0	XPLCK output.
51	GFS	0	GFS output.
52	RFCK	0	RFCK output.
53	VSS	_	GND.
54	C2PO	0	C2PO output.
55	XROF	0	XROF output.
56	MNT3	0	MNT3 output.
57	MNT1	0	MNT1 output.
58	MNTO	0	MNT0 output.
59	FSTT	0	2 divided 3 frequency output of pins 73 and 74.
60	C4M	0	4.2336MHz output.
61	DOUT	0	Digital Out output pin.
62	EMPH	0	H when emphasis of playback disc is present and L for absent.
63	EMPHI	ı	Deemphasis ON/OFF of DAC. (H:ON, L:OFF)
64	WFCK	0	WFCK(WRITE FRAME CLOCK) output.
65	ZEROL	0	Blank sound data detecting output. "H"(Lch) when detecting blank sound data.
66	ZEROR	0	Blank sound data detecting output. "H" (Rch) when detecting blank sound data.
67	DTS1	ı	Test pin 1 for DAC. Normally L.
68	VDD	_	Digital power supply for DAC.
69	NLPWM	0	Lch PWM output. (Negative phase)
70	LPWM	0	Lch PWM output. (Positive phase)
71	AVDD2	_	Power supply for Lch PWM driver.
72	AVDD3	-	Power supply for Xtal.
73	XTAI	1	Xtal oscillation circuit input of 33.8688MHz
74	XTAO	0	Xtal oscillation circuit output of 33.8688MHz
75	AVSS3	_	GND for Xtal.
76	AVSS2	-	GND for PWM driver.
77	NRPWM	0	Rch PWM output. (Negative phase)
78	RPWM	0	Rch PWM output. (Positive phase)
79	DTS2	1	Test pin 2 for DAC. Normally L.
80	DTS3	ı	Test pin 3 for DAC. Normally L.

- •PCMD is 2'S complement output of MSB fast.
- •PGMD is 2'S complement output of MSB fast.
 •GTOP is monitored the protection state of Frame sync. (H : Open the sync. protection window)
 •XUGF is frame sync. which is obtained from the EFM signal, is the negative pulse. This signal is former sync. protection.
 •XPLCK is made PLL to agree the change point of the clock inversion of EFM PLL, falling edge and EFM signal.
 •GFS signal will be H when agreeing with the frame sync. and internal insertion protection timing.
 •RFCK is 136 μ period signal which is obtained by Xtal precision.
 •C2PO is the signal which indicating the data error state.
 •XRAOF signal is generated when 16K RAM is overed the jitter margin of \pm 4F

9. DISASSEMBLY

■ REMOVE THE FRONT PANEL

- 1 Remove the bonnet.
- 2 4 Remove the screws and parts.

Note: Remove the screw in step (4) with the hood closed.

A Remove the fixing screw in step from the disc rack, then remove the hook from disc rack boss.





Fig. 2

⑤ - ⑥ Remove each part and wire.



- TRemove the front panel.
- Shift the front panel slightly toward you while paying attention to the right and left hooks on the chassis. (Fig.2)

10. PANEL FACILITIES


■ FRONT PANEL TIME button CLEAR button HI-LITE button **RANDOM** button Hood MODE button **REPEAT** button 8 88 8 **BEST** button PREVIOUS button DISC(-,+)button C-90Fu PROGRAM button 1 POWER STANDBY/ON switch Track /Manual search

Play /pause button (►/III)

buttons (I◄◄◄◄/►►►►I)

Stop button (■)

DISPLAY



11. SPECIFICATIONS

1. General Type Compact disc digital audio system Power requirements U.S. and Canadian models..... AC 120V, 60 Hz U K.,European models AC 220 - 240V, 50/60 Hz Australian New Zealand models AC 220 -240V, 50/60 Hz Power consumption Operating temperature +5°C - +35°C (+41°F - +95°F) (+41°F - +95°F) Weight (without package) 4.8 kg (10 lb 9 oz.) External dimensions 420(W) X 316(D) X 190(H) mm 16-9/16(W) X 12-7/16(D) X 7-1/2(H) in. 2. Audio section Frequency response 2 Hz - 20 Hz Level difference between channels 1 0 dB or less (EIAJ) Wow and flutterless than ±0.001 % (W.PEAK) (below measurable level) (EIAJ)


3. Output terminal

Audio line output Control input/output jacks(PD-F505 and U.S., Canadian, Australian and New Zealand models of PD-F605 only) Optical digital output jack(PD-F605 only)

NOTE

Specifications and design subject to possible modification without notice, due to improvements.

12. BLOCK DIAGRAM



1. SAFETY INFORMATION

VARO! — AVATTAESSA JA SUOJALUKITUS OHITETTAESSA OLET ALTTIINA NÄKYMÄTTÖMÄLLE LASERSÄTEILYLLE. ÄLÄ KATSO SÄTEESEEN.

- ADVERSEL:
USYNLIG LASERSTRÅLING VED ÅBNING
NÅR SIKKERHEDSAFBRYDERE ER UDE AF
FUNKTION UNDGÅ UDSAETTELSE FOR

STRÄLING.

- VARNING!
OSYNLIG LASERSTRÅLNING NÄR DENNA
DEL ÄR ÖPPNAD OCH SPÄRREN
ÄR URKOPPLAD. BETRAKTA EJ STRÅLEN.



LASER Kuva 1 Lasersateilyn varoitusmerkki

WARNING!

DEVICE INCLUDES LASER DIODE WHICH EMITS INVISIBLE INFRARED RADIATION WHICH IS DANGEROUS TO EYES. THERE IS A WARNING SIGN ACCORDING TO PICTURE 1 INSIDE THE DEVICE CLOSE TO THE LASER DIODE




LASER
Picture 1
Warning sign for laser radiation

- IMPORTANT -

THIS PIONEER APPARATUS CONTAINS LASER OF CLASS 1.
SERVICING OPERATION OF THE APPARATUS SHOULD BE DONE BY A SPECIALLY INSTRUCTED PERSON.

---- LASER DIODE CHARACTERISTICS -MAXIMUM OUTPUT POWER: 5 mw WAVELENGTH: 780-785 nm

LABEL CHECK (for WPWXJ, WVXJ, WYXJ and RLXJ types)



2. CONTRAST OF MISCELLANEOUS PARTS

NOTES:

- Parts marked by "NSP" are generally unavailable because they are not in our Master Spare Parts List.
- The \triangle mark found on some component parts indicates the importance of the safety factor of the part. Therefore, when replacing, be sure to use parts of identical designation.
- Parts marked by " " are not always kept in stock. Their delivery time may be longer than usual or they may be unavailable.
- When ordering resistors, first convert resistance values into code form as shown in the following examples.
 Ex.1 When there are 2 effective digits (any digit apart from 0), such as 560 ohm and 47k ohm (tolerance is shown by J = 5%, and K = 10%)

560Ω	\rightarrow	$56 \times 10^{1} \rightarrow 561 \dots$	RDI/4PU5611J
.,		$47 \times 10^3 \rightarrow 473$	
0.5Ω	\rightarrow	0R5	RN2HORSK
		IRO	

Ex.2 When there are 3 effective digits (such as in high precision metal film resistors). 5.62k $\Omega \rightarrow 562 \times 10^{\circ} \rightarrow 5621$ RN1/4PC S621 F

■ CONTRAST OF PD-F605/WYXJ, WVXJ, WPWXJ, RDXJ AND RLXJ TYPES

PD-F605/WYXJ, WVXJ, WPWXJ, RDXJ, RLXJ and PD-F605/KUXJ have the same construction except for the following:

				Part	No.			
Mark	Symbol & Description	PD-F605 /KUXJ	PD-F605 /WYXJ	PD-F605 /WVXJ	PD-F605 /WPWXJ	PD-F605 /RDXJ	PD-F605 /RLXJ	Remarks
Δ	Mother PCB Assy	PWM1989	PWM1990	PWM1990	PWM1996	PWM1993	PWM1991	
NSP	SUB PCB Assy	PWX1434	PWX1435	PWX1435	PWX1435	PWX1435	PWX1435	
1,12.	-Function PCB Assy	PWZ3134	PWZ3135	PWZ3135	PWZ3135	PWZ3135	PWZ3135	
NSP	Power SW PCB Assy	PWZ3145	PWZ3146	PWZ3146	PWZ3146	PWZ3146	PWZ3146	·
Δ	Power transformer (AC120V)	PTT1237	Not used	Not used	Not used	Not used	Not used	
\triangle	Power transformer (AC220 – 240V)	Not used	PTT1236	PTT1236	PTT1236	Not used	Not used	}
Δ	Power transformer (AC110 – 127V/220 – 240V)	Not used	Not used	Not used	Not used	PTT1238	PTT1238	
Δ	AC Power Cord	PDG1015	PDG1003	PDG1055	ADG1123	PDG1056	PDG1003	
$\overline{\Lambda}$	Fuse (T5A) (For AC power cord)	Not used	Not used	PEK1003	Not used	Not used	Not used	*1. No.1
Δ	Strain Relief	CM – 22C	CM – 22B	CM – 22B	CM – 22B	CM – 22B	CM - 22B	
	Rear Base	PNA2258	PNA2261	PNA2261	PNA2287	PNA2288	PNA2289	
	Foot Assy	AEC1531	Not used	Not used	Not used	AEC1531	Not used	
	Insulator	Not used	PNW1912	PNW1912	PNW1912	Not used	PNW1912	★ 1. No.2
	Rubber Sheet	AEB1111	Not used	Not used	Not used	AEBIIII	Not used	
	Control Panel	PNW2649	PNW2653	PNW2653	PNW2653	PNW2654	PNW2653	
	Display Window	PAM1702	PAM1714	PAM1714	PAM1702	PAM1702	PAM1702	
	LED Lens	Not used	PNW2019	PNW2019	PNW2019	PNW2019	PNW2019	≭ 1. No.3
	Caution Label (HE)	Not used	PRW1233	Not used	Not used	Not used	Not used	★ 1. No.4
	Caution Label (F)	Not used	VRW - 328	VRW – 328	VRW - 328	Not used	VRW - 328	★ 1. No.5
	Caution Label (G)	Not used	VRW - 329	VRW - 329	VRW - 329	Not used	VRW - 329	≱ 1. No.6
	Caution Label	Not used	Not used	PRW1018	PRW1018	Not used	PRW1018	★1 . No.7
	Caution Label	Not used	VRW1094	Not used	Not used	Not used	Not used	★ 1. No.8
	65 Label	ORW1069	Not used	Not used	Not used	Not used	Not used	
	Packing Case	PHG2162	PHG2164	PHG2190	PHG2205	PHG2191	PHG2205	
	Index Label	Not used	PRW1422	PRW1422	PRW1422	PRW1422	PRW1422	*1. No.9
	Caution 220V Label	Not used	Not used	Not used	Not used	ARR1003	ARR1003	*1. No.10
	Liner Note File	Not used	PHN1051	PHN1051	PHN1051	PHN1051	PHN1051	*1. No.11
	Rear Spacer	Not used	Not used	PHC1087	Not used	Not used	Not used	*1. No.12
	Operating instructions (English)	PRB1234	PRB1234	PRB1234	PRB1234	Not used	Not used	
	Operating instructions (English/Spanish/Chinese)	Not used	Not used	Not used	Not used	PRE1226	PRE1226	
	Operating instructions (French/German/Italian/Dutch /Swedish/Spanish/Portuguese)	Not used	PRD1006	Not used	Not used	Not used	Not used	
	Cord with Mini Plug	PDE1247	Not used	Not used	PDE1247	Not used	Not used	
NSP	Warranty card	ARY1051	ARY7009	ARY7009	PRY 1003	Not used	Not used	

Note *1: The numbers in the remarks column correspond to the numbers on the exploded views.

PD-F605, PD-F505

■ CONTRAST OF PD-F505/WPWXJ AND RDXJ TYPES


PD-F505/WPWXJ, RDXJ and PD-F505/KUXJ types have the same construction except for the following:


			Part No.		Remarks
Mark	Symbol & Description	PD-F505/KUXJ	PD-F505/WPWXJ	PD-F505/RDXJ	Hemarks
Δ	Mother PCB Assy	PWM1984	PWM1985	PWM1988	
NSP	SUB PCB Assy	PWX1429	PWX1430	PWX1430	-
Nor	-Function PCB Assy	PWZ3129	PWZ3130	PWZ3130	
NSP	Power SW PCB Assy	PWZ3143	PWZ3144	PWZ3144	
Δ	Power transformer (AC120V)	PTT1237	Not used	Not use	
\triangle	Power transformer (AC220 – 240V)	Not used	PTT1236	Not used	
$\overline{\Delta}$	Power transformer	Not used	Not used	PTT1238	1
	(AC110 - 127V/220 - 240V)				
Δ	AC Power Cord	PDG1015	ADG1123	PDG1056	
$\overline{\Delta}$	Strain Relief	CM - 22C	CM – 22B	CM – 22B	
	Rear Base	PNA2241	PNA2290	PNA2291	
	Foot Assy	AEC1531	Not used	AEC1531	
	Insulator	Not used	PNW1912	Not used	★1. No.2
	Rubber Sheet	AEB1111	Not used	AEB1111	
	Control Panel	PNW2617	PNW2651	PNW2652	
	32P F.F.C/30V	PDD1167	Not used	Not used	
	34P F.F.C/30V	Not used	PDD1168	PDD1168	* 2
	LED Lens	Not used	PNW2019	PNW2019	≭ 1. No.3
	Caution Label (F)	Not used	VRW - 328	Not used	★ 1. No.5
	Caution Label (G)	Not used	VRW – 329	Not used	★ 1. No.6
	Caution Label	Not used	PRW1018	Not used	★ 1. No.7
	65 Label	ORW1069	Not used	Not used	
	Packing Case	PHG2156	PHG2204	PHG2192	
	Index Label	Not used	PRW1422	PRW1422	≄ 1. No.9
	Caution 220V Label	Not used	Not used	ARR1003	★ 1. No.10
	Liner Note File	Not used	PHN1051	PHN1051	≭ 1. No.11
	Operating instructions (English)	PRB1234	PRB1234	Not used	
	Operating instructions (English/Spanish/Chinese)	Not used	Not used	PRE1226	
NSP	Warranty Card	ARY1051	PRY1003	Not used	

Note *1: The numbers in the remarks column correspond to the numbers on the exploded views.

^{*2 :} Refer to "PCB CONNECTION DIAGRAM"

PACKING





■ CONTRAST OF PCB ASSEMBLIES FOR PD-F605

MOTHER PCB ASSY

PWM1990, PWM1996, PWM1993, PWM1991 and PWM1989 have the same construction except for the

		Part No.					
Mark	Symbol & Description	PWM1989	PWM1990	PWM1996	PWM1993	PWM1991	Remarks
	CI22	Not used	CEAS100M16	Not used	Not used	Not used	
	C132	CGCYX473K25	Not used	Not used	CGCYX473K25	Not used	
	C302, C304	CFTYA104J50	CEAS471M6R3	CEAS471M6R3	CFTYA104J50	CEAS471M6R3	
	C303	CKCYF103Z50	Not used	Not used	CKCYF103Z50	Not used	
	C310				CCCCH100D50	Not used	
	C341	CCCCH100D50	Not used	Not used	CCCCH100D30	Not used	
	C342	CKCYB102K50	Not used	Not used	CKCYB102K50	Not used	
	C343	CCCCH220J50	Not used	Not used	CCCCH220J50	Not used	
	C368	Not used	CKCYB102K50	CKCYB102K50	Not used	CKCYB102K50	
	C393	CCCSL101J50	Not used	CCCSL101J50	Not used	Not used	
	C403	Not used	CCCCH120J50	CCCCH120J50	Not used	CCCCH120J50	
	C404	Not used	CCCCH220J50	CCCCH220J50	Not used	CCCCH220J50	
	C413 - C416	Not used	CFTYA104J50	CFTYA104J50	Not used	CFTYA 104J50	
	C417	Not used	CGCYX104K25	CGCYX104K25	Not used	CGCYX104K25	i
	C421, C422	CKCYB471K50	Not used	Not used	CKCYB471K50	Not used	
	C423 – C426	CCCSL181J50	Not used	Not used	CCCSL181J50	Not used	
	C429, C430	Not used	CCCCH390J50	CCCCH390J50	Not used	CCCCH390J50	
	C432	Not used	CEAS470M25	CEAS470M25	Not used	CEAS470M25	
		CEANP220M10	CEAS220M25	CEAS220M25	CEANP220M10	CEAS220M25	
	C433, C434	CCCSL101J50	CCCCH390J50	CCCCH390J50	CCCSL101J50	CCCCH390J50	
	C435 – C438	CKCYB152K50	PCL1030	PCL1030	CKCYB152K50	PCL1030	1
	C441, C442 (1500pF)	CKC1B152K50	PCLIUSU	PCLIOSO	CKC1B132K30		
	C461	Not used	CKCYF103Z50	CKCYF103Z50	Not used	CKCYF103Z50	
	D321, D341	1SS254	Not used	Not used	1SS254	Not used	
	D352	Not used	Not used	Not used	1SS254	Not used	1
	D391 – D394	1SS254	Not used	1SS254	Not used	Not used	
Δ	IC31	Not used	ICP - N10	ICP - N10	ICP - N10	ICP - N10	
	IC401	Not used	PD2026B(L)	PD2026B(L)	Not used	PD2026B(L)	
	JA391, JA392	RKN1004	Not used	RKN1004	Not used	Not used	!
	L302, L303	LAU010J	Not used	Not used	LAU010J	Not used	
	L341	LAU1R2J	Not used	Not used	LAU1R2J	Not used	
	L372	Not used	LAUR47J	LAUR47J	Not used	LAUR47J	
	L391	LAU010J	Not used	LAU010J	Not used	Not used	
	Q322	Not used	DTC124ES	DTC124ES	Not used	DTC124ES	1
	Q341	2SK246	Not used	Not used	2SK246	Not used	
	R310 – R312,	Not used	RD1/4PU471J	RD1/4PU471J	Not used	RD1/4PU471J	
	R405 – R410	1000					
	D241	RD1/4PU511J	Not used	Not used	RD1/4PU511J	Not used	
	R341	RD1/4PU105J	Not used	Not used	RDI/4PU105J	Not used	
	R342, R366	Not used	RD1/4PU221J	RD1/4PU221J	RD1/4PU151J	RDI/4PU221J	
	R351	Not used	RD1/4PU103J	RD1/4PU103J	Not used	RD1/4PU103J	
	R364, R367 R365	RD1/4PU103J	Not used	Not used	RDI/4PU103J	Not used	
		DD1/401044*	NI-A	DD1/4D1/2441	Not used	Not used	
	R391	RD1/4PU244J	Not used	RD1/4PU244J	Not used		
	R392	RDI/4PU102J	Not used	RD1/4PU102J	Not used	Not used	1
	R401	Not used	RDI/4PU102J	RD1/4PU102J	Not used	RD1/4PU102J	1
	R419 - R422	RDI/4PU562J	Not used	Not used	RD1/4PU562J	Not used	
	R427 – R430	RD1/4PU153J	RD1/4PU223J	RD1/4PU223J	RDI/4PU153J	RD1/4PU223J	
	R435 – R438	RD1/4PU333J	RD1/4PU163J	RD1/4PU163J	RD1/4PU333J	RD1/4PU163J	
	R439 – R442	RD1/4PU563J	RD1/4PU433J	RD1/4PU433J	RD1/4PU563J	RD1/4PU433J	
	S5	Not used	Not used	Not used	PSB1006	PSB1006	
	X341 (4.19MHz)	ASS7000	Not used	Not used	ASS7000	Not used	
	X401 (16.9344MHz)	Not used	PSS1008	PSS1008	Not used	PSS1008	

FUNCTION PCB ASSY

Although PWZ3134 and PWZ3135 are diffirent in part number, they consist of the same components.

POWER SW PCB ASSY

PWZ3146 and PWZ3145 have the same construction except for the following:

Mark		Part		
	Symbol & Description	PWZ3145	PWZ3146	Remarks
	D751	Not used	PCX1019	

■ CONTRAST OF PCB ASSEMBLIES FOR PD-F505

MOTHER PCB ASSY

PWM1985, PWM1988 and PWM1984 have the same construction except for the following:

	Symbol & Description	Part No.			Remarks
Mark		PWM1984	PWM1985	PWM1988	nemark
	C302, C304	CGCYX473K25	Not used	CGCYX473K25	
	C303	CFTYA104J50	CEAS471M6R3	CFTYA104J50	
	C310	CKCYF103Z50	Not used	CKCYX103Z50	
	C341	CCCCH100D50	Not used	CCCCH100D50	
		CKCYB102K50	Not used	CKCYB102K50	
	C342	CRC 1 D 102 R 30	1 vot used	CKC I DIOZKSO	
	C343	CCCCH220J50	Not used	CCCCH220J50	
	C368	Not used	CKCYB102K50	Not used	
	C403	Not used	CCCCH120J50	Not used	
	C404	Not used	CCCCH220J50	Not used	
	C413 - C416	Not used	CFTYA 104J50	Not used	
	C417	Not used	CGCYX104K25	Not used	
	C421, C422	CKCYB471K50	Not used	CKCYB471K50	
	C421, C422 C423 – C426	CCCSL181J50	Not used	CCCSL181J50	
		Not used	CCCCH390J50	Not used	
	C429, C430		CEAS470M25	Not used	
	C432	Not used	CEAS470M23	Not used	
	C433, C434	CEANP220M10	CEAS220M25	CEANP220M10	
	C435 - C438	CCCSL101J50	CCCCH390J50	CCCSL101J50	
	C441, C442 (1500pF)	CKCYB152K50	PCL1030	CKCYB152K50	
	C441, C442 (1300pl*)	Not used	CKCYF103Z50	Not used	
		HLEM32S - 1	HLEM34S - 1	HLEM34S - 1	
	CN351	HLEWI325 - I	TILLWISTS - I	I ILLEMS I	
	D341	1SS254	Not used	188254	
	D352	Not used	Not used	1SS254	
Δ	IC31	Not used	ICP - N10	ICP - N10	
	IC401	Not used	PD2026B(L)	Not used	
	L302, L303	LAU010J	Not used	LAU010J	
	L341	LAU1R2J	Not used	LAU1R2J	
	L372	Not used	LAUR47J	Not used	
	Q322	Not used	DTC124ES	Not used	
	0341	2SK246	Not used	2SK246	
	R310 - R312, R405 - R410	Not used	RD1/4PU471J	Not used	
		DD114B115111	Normal	RD1/4PU511J	
	R341	RD1/4PU511J	Not used Not used	RD1/4PU3113 RD1/4PU105J	
	R342, R366	RD1/4PU105J		RD1/4PU151J	
	R351	Not used	RD1/4PU221J		
	R364, R367	Not used	RD1/4PU103J	Not used	
	R365	RDI/4PU103J	Not used	RD1/4PU103J	
	R401	Not used	RD1/4PU102J	Not used	
	R419 - R422	RD1/4PU562J	Not used	RD1/4PU562J	
	R427 - R430	RD1/4PU153J	RD1/4PU223J	RD1/4PU153J	
	R435 – R438	RD1/4PU333J	RD1/4PU163J	RD1/4PU333J	
	R439 – R442	RD1/4PU563J	RD1/4PU433J	RD1/4PU563J	
		Not wood	Not used	PSB1006	
	\$5	Not used		ASS7000	
	X341 (4.19MHz)	ASS7000	Not used	Not used	
	X401 (16.9344MHz)	Not used	PSS1008	NOT USED	

PD-F605, PD-F505

FUNCTION PCB ASSY

PWZ3130 and PWZ3129 have the same construction except for the following:


Mark	Symbol & Description	Part		
		PWZ3129	PWZ3130	Remarks
	CN701	HLEM32R - 1	HLEM34R ~ 1	

POWER SW PCB ASSY

PWZ3144 and PWZ3143 have the same construction except for the following:

Mark		Par		
	Symbol & Description	PWZ3143	PWZ3144	Remarks
	D751	Not used	PCX1019	

The numbers marked with a circle show the number of each measuring point, which correspond to the number in the service manual PD-F605 (ORDER NO. RRV1457) on page13.



7

9

8



Service Manual

ORDER NO. **RRV 1604**

FILE-TYPE CD PLAYER

-605 PD-F505

● Refer to the service manual RRV1457 for PD-F605/KUXJ.

THIS MANUAL IS APPLICABLE TO THE FOLLOWING MODEL(S) AND TYPE(S).

T	Model		Power Requirement	The voltage can be converted by the
Type	PD-F605 PD-F505		Power nequirement	following method.
WPWXJ	0	0	AC220 - 240V	
WYXJ	0	×	AC220 – 240V	
WVXJ	0	×	AC220 – 240V	
RDXJ	0	0	AC110 - 127V/220 - 240V	With the voltage selector
RLXJ	0	×	AC110 - 120V/220 - 240V	With the voltage selector

CONTENTS

1.	SAFETY INFORMATION	2
2.	CONTRAST OF MISCELLANEOUS PARTS	3

PIONEER ELECTRONIC CORPORATION

4-1, Meguro 1-Chome, Meguro-ku, Tokyo 153, Japan

PIONEER ELECTRONICS SERVICE, INC. P.O.Box 1760, Long Beach, CA 90801-1760, U.S.A.
PIONEER ELECTRONIC [EUROPE] N.V. Haven 1087, Keetberglaan 1, 9120 Melsele, Belgium
PIONEER ELECTRONICS ASIACENTRE PTE. LTD. 501 Orchard Road, #10-00 Lane Crawford Place, Singapore 0923

© PIONEER ELECTRONIC CORPORATION 1996

T-FFR APR. 1996 Printed in Japan